

# **METALFORM**

**MASTERS OF METAL**

**Stainless Steel OS2 75 Inward and Outward  
Opening Doors and Windows | Tilt and Turn |**

# METALFORM

## Stainless Steel OS2 75 Inward and Outward Opening Doors and Windows | Tilt and Turn I

- Supply and installation of doors, windows, and facades, including fixed and openable sashes, designed for inward and outward opening doors and windows. These are built with thermal break profiles from Secco Sistemi OS2 75. The frame sections are constructed by seamlessly joining two metal shells, one whole and one external, using extruded polyamide filled with fiberglass and joined to the parts by high-density polyurethane resin. The metal shells are formed by cold-rolling profiling strips of AISI 316L Marine stainless steel, with a thickness in line with 15/10, EN10088-2, and EU114 standards, featuring a Scotch Brite finish.
- The folding unit remains open to facilitate the insertion of stainless steel alignment brackets, even in cases of continuous surface welding. Assembly of the frames involves continuous welding of the contact surfaces, followed by grinding and restoration of the surface finish. The system allows for the internal and external overlapping of the profiles, with minimally visible sections as follows: fixed side node measuring 27 mm, side sash node measuring 47 mm, central node for the two wings measuring 62 mm, and a mandatory depth of 77 mm.
- The frames are equipped with a water, air, and wind sealing system, including triple mortise gaskets for inward opening windows (with two sealing levels, one of which is open-joint), and double mortise gaskets for outward opening windows and doors (with one level of closed joint gasket). Mobile sills for floors are provided for doors, along with a sufficient number of Corten steel screw-on water drains in the windows. The frames come complete with glass, fixed with glazing beads in AISI316L stainless steel, spaced from external surfaces by EPDM or silicone gaskets, and from internal surfaces by pressure-inserted EPDM gaskets.

# METALFORM

- Windows and doors, when there is no tilting sash, are equipped with hinges to be screwed on, stainless adjustable, available with two wings (Ø12 mm for capacities up to 50 kg per sash) or with three wings (Ø15 mm for capacities up to 100 kg per sash). Tilt&Turn/sash window opening is facilitated with concealed hinges (130 kg load-bearing capacity) and outer hardware with an appropriate number of locking points depending on the sash size. An internal bolt locking system with a lower and upper end, along with a sufficient number of additional locking points, is provided for the size of the opening doors. The doors are complete with locks featuring various locking points depending on the height of the sashes and lock cover boxes/reinforced profiles in stainless steel.
- Surfaces are oxidized with Scotch Brite finish. The handles complete the set and are available in different shapes, materials, and finishes, including stainless steel.

# METALFORM

**MASTERS OF METAL**

**UNITED KINGDOM**

**METALFORM**

**NORWAYMETAL LTD**

53 Chelsea Manor Street

London, SW3 5RZ

**SALES@METALFORM.UK**

**+44 20 81298814**

**GERMANY**

**METALFORM GMBH**

Carl-Zeiss-Ring 15A

85737 Ismaning

**SALES@METALFORMGROUP.DE**

**+49 17663630406**

**NORWAY**

**METALFORM AS**

Brochmannsveien 2

1950 Rømskog

**SALG@METALFORM.NO**

**+47 401 62 446**

**METALFORMGROUP**

**SALES@METALFORMGROUP.COM**